



12DS7-A

12DS7-A

TWIN DIODE-POWER TETRODE

9-PIN MINIATURE TYPE

For use in automobile radio receivers
operating directly from 6-cell storage-battery systems

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage range (AC or DC) 10 to 15.9 volts

*This voltage range is on an absolute basis. For long-
est life, it is recommended that the heater be operated
within the voltage range of 11 to 14 volts.*

Current (Approx.) at 12.6 volts 0.4 amp

Direct Interelectrode Capacitances:^o

Tetrode Unit:

Grid No.2 to plate. 13.8 μf

Grid No.2 to grid No.1, cathode,
and heater. 12.7 μf

Plate to grid No.1, cathode,
and heater. 2.2 μf

Diode Units:

Diode plate No.1 to cathode
and heater. 0.5 μf

Diode plate No.2 to cathode
and heater. 0.5 μf

Diode plate No.1 to diode plate No.2. 0.1 μf

Tetrode grid No.2 to diode plate No.1 0.3 μf

Tetrode grid No.2 to diode plate No.2 0.3 μf

Characteristics, Class A₁ Amplifier (Tetrode Unit):

Heater Voltage. 12.6 volts

Plate Voltage 12.6 volts

Grid-No.2 Voltage:

Developed across a 2.2-megohm resistor. -0.5 volt

Grid-No.1 Voltage 12.6 volts

Plate Resistance (Approx.) 500 ohms

Amplification Factor, Grid No.2 to Plate. 9.1

Transconductance, Grid No.2 to Plate. 19000 μmhos

Plate Current 35 ma

Grid-No.1 Current 75 ma

Mechanical:

Operating Position. Any

Maximum Overall Length. 2-5/8"

Maximum Seated Length 2-3/8"

Length, Base Seat to Bulb Top (Excluding tip) 2" $\pm$ 3/32"

Diameter. 0.750" to 0.875"

Dimensional Outline See General Section

Bulb. T6-1/2

Base. Small-Button Noval 9-Pin (JEDEC No.E9-1)

12DS7-A



12DS7-A


TWIN DIODE-POWER TETRODE

Basing Designation for BOTTOM VIEW. 9JU

Pin 1-Plate of Diode
Unit No.2Pin 2-No Connec-
tionPin 3-Grid No.1 of
Tetrode Unit

Pin 4-Heater

Pin 5-Heater

Pin 6-Plate of
Tetrode UnitPin 7-Grid No.2 of
Tetrode Unit

Pin 8-Cathode

Pin 9-Plate of Diode
Unit No.1

TETRODE UNIT — AUDIO DRIVER

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	16 max. volts
GRID-No.2 (CONTROL-GRID) VOLTAGE:	
Negative-bias value	16 max. volts
GRID-No.1 (SPACE-CHARGE-GRID) VOLTAGE .	16 max. volts
PEAK HEATER-CATHODE VOLTAGE:	
Heater negative with respect to cathode.	16 max. volts
Heater positive with respect to cathode.	16 max. volts

Typical Operation:

Cathode Bias

Heater Voltage.	12	volts
Plate Supply Voltage.	11.2	volts
Plate Voltage	Obtained from indicated plate supply through series 100-henry choke having dc resistance of 150 ohms	
Grid-No.2 Supply Voltage.	0	volts
Grid-No.2 Resistor.	1.8	megohms
Grid-No.1 Supply Voltage.	11.2	volts
Cathode Resistor.	18	ohms
Peak AF Grid-No.2 Supply Voltage (Approx.):		
From 3.3-megohm signal source	4.25	volts
Zero-Signal Plate Current (Approx.) . .	20	ma
Indicated-Signal Plate Current.	7	ma
Grid-No.1 Current	58	ma
Load Resistance	1250	ohms
Total Harmonic Distortion at power output of 2.5 mw.	5	%
Indicated-Signal Power Output	10	mw

Grid-No.2-Resistor Bias

Heater Voltage.	12.6	volts
Plate Voltage	12.6	volts
Grid-No.2 Voltage:		
Obtained by rectification through a 2.2-megohm resistor	-2.5	volts



12DS7-A

12DS7-A

TWIN DIODE-POWER TETRODE

Peak AF Grid-No.2 Voltage (Approx.):		
From 0.22-megohm signal source. . . .	2.5	volts
Grid-No.1 Voltage	12.6	volts
Zero-Signal Plate Current (Approx.) . .	35	ma
Max.-Signal Plate Current	11	ma
Grid-No.1 Current	80	ma
Load Resistance	700	ohms
Total Harmonic Distortion	10	%
Max.-Signal Power Output.	45	mw

Maximum Circuit Values:

Grid-No.2-Circuit Resistance.	10 max.	megohms
---------------------------------------	---------	---------

DIODE UNITS — Two

Values are for Each Unit

Maximum Ratings, Design-Maximum Values:

PLATE CURRENT	5 max.	ma
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	16 max.	volts
Heater positive with respect to cathode.	16 max.	volts

Characteristics:

Heater Voltage.	12.6	volts
Plate Current for plate volts = 10. . .	3	ma

^o Without external shield.


2DS7-A



12DS7-A

AVERAGE PLATE CHARACTERISTICS TETRODE UNIT

$E_f = 12.6$ VOLTS
GRID-№1 (SPACE-CHARGE-GRID) VOLTS = 12.6



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-10136



12DS7-A

AVERAGE CHARACTERISTICS TETRODE UNIT

12DS7-A

